



KEY:
 SL - STORAGE LENGTH (FEET)
 D - DISTANCE BETWEEN ARROWS AND LEGENDS (FEET)

- GENERAL NOTES:**
1. THESE DETAILS ALSO APPLY TO RIGHT-TURN LANES.
 2. FOR DUAL-TURN LANES, DIMENSIONS SHALL BE THE SAME FOR EACH LANE.
 3. SL DIMENSION IS FROM STOP LINE TO END OF TURN LANE, WHICH DOES NOT INCLUDE TAPER LENGTH.
 4. PAVEMENT ARROWS AND "ONLY" LEGEND MARKINGS ARE TYPICALLY USED AT SIGNALIZED INTERSECTIONS AND AT UNSIGNALIZED INTERSECTIONS WHERE A DEMONSTRATED NEED EXISTS.
 5. MINIMUM SL = 110'. SL MAY BE LESS THAN 110 FEET AS DIRECTED BY THE CITY TRAFFIC ENGINEER.

SEPTEMBER 2009
 CITY OF SAN ANTONIO
 DEPARTMENT OF PUBLIC WORKS
 TRAFFIC ENGINEERING STANDARDS
**LEFT-TURN "ONLY" AND ARROW
 SPACING WORKSHEET**
 SHEET 1 OF 16

SUBMITTAL	PROJECT NO.:	DATE:	
DRWN. BY: LAN	DSGN. BY: C.B.W.	CHKD. BY: M.E.	SHEET NO.: OF